



Fabrication and characterization of shunted -SQUID

Nikhil Kumar, T. Fournier, H. Courtois, and Anjan K. Gupta

Citation: [AIP Conference Proceedings](#) **1591**, 1591 (2014); doi: 10.1063/1.4873045

View online: <http://dx.doi.org/10.1063/1.4873045>

View Table of Contents: <http://scitation.aip.org/content/aip/proceeding/aipcp/1591?ver=pdfcov>

Published by the [AIP Publishing](#)

Articles you may be interested in

[Fabrication and characterization of a capacitive micromachined shunt switch](#)

J. Vac. Sci. Technol. A **22**, 1383 (2004); 10.1116/1.1690255

[Performance of dc SQUIDs with resistively shunted inductance](#)

Appl. Phys. Lett. **55**, 1451 (1989); 10.1063/1.101583

[Noise characteristics of a dc SQUID with a resistively shunted inductance. II. Optimum damping](#)

J. Appl. Phys. **60**, 4218 (1986); 10.1063/1.337510

[Resistively shunted dc SQUID coupled to an input coil](#)

J. Appl. Phys. **59**, 1714 (1986); 10.1063/1.336436

[Noise characteristics of a dc SQUID with a resistively shunted inductance](#)

J. Appl. Phys. **58**, 1916 (1985); 10.1063/1.335998
